

DATA SHEET

SFP+ 10GBASE-LR/LW / I-64.1 / 10G FC, 1310NM SMF 10KM TRANSCEIVER EXTENDED TEMPERATURE

DESCRIPTION

This transceiver is hot pluggable duplex-LC optical transceiver designed for using in 10Gbps serial applications such as SONET OC192/SDH STM64, 10Gigabit Ethernet and 10Gbps Fiber Channel applications. It operates with single +3.3V power supplies. The transceiver conforms to the 10Gbps SFP+ multi-source agreement (MSA).

This transceiver consists of optical subassemblies (OSA) for both transmitter and the receiver, and an electrical subassembly, which is packaged together in a metal enclosure. The TOSA is a high-performance 1310nm DFB with isolator, and the ROSA is high speed PIN type detector with a built-in preamplifier.



KEY FEATURES

1310nm DFB and PIN receiver

LVTTTL (open collector) digital diagnostic monitoring signals

Compliant with specifications for IEEE-802.3ae 10Gigabit Ethernet at 10.3Gbps and 10G Fiber Channel at 10.52Gbps

Conforms to 10Gbps SFP+ Multi-Source Agreement

Class 1 Laser Safety Conformance

Compatible with industry standard SFP electrical connector & cage

Industry standard duplex LC optical connector

Operates with 9/125 μ m signal-mode optical fibers

Case temperature range : -40°C to 85°C

APPLICATIONS

10G Ethernet at 10.3125Gbps for up to 10km reach

10G Fiber channel at 10.5187Gbps

OC192 over FEC at 10.709Gbps

SDH STM-64/SONET OC192 at 9.953Gbps

COMPLIANCES

Compliant with SFF-8472 SFP+ MSA.

Compliant to SFP+ SFF-8431 and SFF-8432.

RoHS Compliant6

DATA SHEET

SFP+ 10GBASE-LR/LW / I-64.1 / 10G FC, 1310NM SMF 10KM TRANSCEIVER EXTENDED TEMPERATURE

ENVIRONMENTAL SPECIFICATIONS

| Parameter | Min. | Typ. | Max. | Unit |
|-----------------------|------|-------|------|------|
| Operation Temperature | -40 | | +85 | °C |
| Storage Temperature | -40 | ----- | +85 | °C |
| Operation Humidity* | 5 | ----- | 85 | % |
| Storage Humidity | 5 | ----- | 85 | % |

(*) not condensing

OPERATING SPECIFICATIONS

| Parameter | Min. | Typ. | Max. | Unit |
|-----------------------|------|------|------|------|
| Supply Voltage | 3.1 | +3.3 | +3.5 | V |
| Power Dissipation | | 2.4 | | W |
| Transmission Distance | | | 10 | Km |

OPTICAL SPECIFICATIONS

TRANSMITTER

| Parameter | Min. | Typ. | Max. | Unit |
|-----------------------|------|------|------|------|
| Input Wavelength | 1270 | 1310 | 1355 | nm |
| Average Launch Power | -8.2 | - | 0.5 | dBm |
| Extinction Ratio (ER) | 3.5 | | | dB |
| SMSR | 30 | | | dB |
| Bandwidth@-20dB | | | 1 | nm |

RECEIVER

| Parameter | Min. | Typ. | Max. | Unit |
|-----------------------------------|------|------|-------|------|
| Input Wavelength | 1100 | | 1600 | nm |
| Receiver Sensitivity | | | -12.6 | dBm |
| Input Saturation Power (Overload) | 0 | | | dBm |
| LOSA | -25 | | | dBm |
| Hysteresis | 0.5 | | 5 | dB |

DATA SHEET

SFP+ 10GBASE-LR/LW / I-64.1 / 10G FC, 1310NM SMF 10KM TRANSCEIVER EXTENDED TEMPERATURE

ORDERING INFORMATION

| Jabil Part Number | Package | Rate | Reach | Other info |
|-------------------|---------|------|-------|-------------------------------|
| JPSP10LRLCE000L13 | SFP+ | 10G | 10Km | DDM/RoHS Extended Temperature |

For additional information, visit jabil.com/photonics